

PRECISION ELECTROPLATED SOLDER BUMPS AND METHOD FOR MANUFACTURING
THEREOF

by

DANIEL YAP

and

PHILLIP H. LAWYER

145A1>

I. BACKGROUND OF THE INVENTION

1. Field of the Invention.

This invention relates to the field of solder bump structures compatible with group III-V semiconductor materials. More particularly, the present invention pertains to the use of a novel electroplating method of fabrication of the solder bumps which method does not damage air bridges, micro-electromechanical structures, or optical surfaces that can be otherwise damaged if conventional methods for fabricating solder bumps are used.

2. Description of the Related Art.

Prior or related art teaches methods of fabrication of a number of solder bump structures. The prior art methods include a

method of vacuum evaporation and a method of electroplating.

The structure shown in Figure 1(a) contains a solder bump formed by deposition in a vacuum evaporator. See W. R. Imler, et al., IEEE Transactions on Components, Hybrids, and Manufacturing Technology, v. 15, p. 977, 1992. The solder bump resides above a multilayer pad that consists of titanium, tungsten nitride, nickel alloy, and gold. This structure also contains an oxidized silicon passivation film which serves as a non-wettable dam to constrain the solder wet back. The solder bumps are deposited through metal shadow masks clamped over the surface of the substrate wafer. A solder pad diameter of 75 micrometers at a pitch of 156 micrometers has been achieved with this technique. A disadvantage of the shadow-masked evaporation method is that solder bumps having smaller diameter and finer pitch are difficult to achieve yet such smaller diameter and finer pitch bumps are often needed.

The structure shown in Figure 1(b) contains a solder bump formed by electroplating. See T. Kawanobe, K. Miyamoto, and Y. Inaba, IEEE publication CH1671-7/0000, p. 149, 1981. The solder bump resides on multilayer underbump metallization (hereinafter, UBM) that consists of titanium and copper films and an electroplated

nickel pad. A 2 micrometer thick copper film serves as a plating membrane for the electroplating of the lead/tin solder. The titanium film is designed to serve as an adhesion layer between the copper film and the underlying aluminum metallization, passivation film or silicon substrate. After the electroplating, the copper and titanium films are wet etched away, leaving only a small pad of UBM material underneath the solder. Electroplated solder bumps can have quite fine pitch, e.g. 50 micrometer diameter pads with 100 micrometer pitch is typical.

However, when the solder bump is formed by electroplating, the plating membrane must be removed subsequently in order to avoid short circuiting the various solder bump joints that exist on a substrate. It is difficult to find suitable underbump metallization and plating membrane materials that can be etched away without also attacking the solder or the underlying circuitry. Copper is typically used as the plating membrane because its etchant does not attack the lead/tin solder. Copper, however, is not compatible with group III-V semiconductor materials. In addition to avoiding an attack on the solder bump itself, some provision is needed to protect the circuit elements from attack by the plating bath and by the etchants used to remove the membrane. In the structure of Figure 1(b), a

permanent passivation film, formed underneath the UBM and typically consisting of silicon dioxide or polyimide, protects the circuit elements. That passivation film also serves as a non-wettable surface or solder dam which causes the plated solder to wet back onto the pad.

The known electroplating method described above has some serious disadvantages and is not usable with group III-V semiconductor materials. In addition to the impossibility to use copper due to its incompatibility with group III-V semiconductor materials, for some MMICs, microelectromechanical elements or optoelectronic devices, it may not be possible to protect key features such as air bridges, cantilever beams or optical coatings and surfaces with a permanent passivation film. A removable protective film is needed. Another need is to have a solder dam that covers only the vicinity of the solder bump. Also needed is a plating membrane that both is compatible with group III-V materials and that can be etched away without attacking the plated solder.

For the foregoing reasons, there is a need for a method of fabrication of a solder bump having a small diameter and a very fine pitch, where a removable protective film is utilized. The plating membrane is needed that is compatible with group III-V

semiconductor materials and that can be etched away without attacking the plated solder. The present invention offers such a solder bump and the method of manufacturing thereof.

II. SUMMARY OF THE INVENTION

The present invention is directed to a method of fabrication of a solder bump allowing to obtain very fine size bumps while a solder dam preferably only covers space in a vicinity of the bump. The method uses a plating membrane compatible with group III-V semiconductor materials and also with group IV semiconductor materials. After the completion of the fabrication process, the membrane is safely removed and the solder is unaffected by the agent used to remove the membrane. This invention is also directed to the solder bump structure obtained as a result of utilization of this method.

The solder bump structure and fabrication method of this invention avoid the need for depositing a permanent layer over the circuits to protect them from the solder-bump processing. Such a permanent layer can alter the performance of the circuits and devices. In accordance with the invention it is now possible to fabricate electroplated solder bumps while simultaneously

protecting the circuit elements from such altered performance. For example, circuits for wireless communications may contain inductors, transmission lines or transistors that have air bridges which would be adversely affected by a permanent layer such as one found in the prior art. Also, future high-speed, high-density interconnects between processors may be based on chips of solder-bumped optoelectronic devices which also should not be covered by such a layer.

This invention uses a metal film, preferably of titanium, deposited above the protective film, to serve both as a plating membrane and a solder dam and uses a photodefinable polyimide, a spin-on glass, a spin-on conductive polymer, or, preferably, a photoresist as a removable protective film. The photoresist can be removed, after the solder plating and membrane etching, by solvents that do not attack the solder. The titanium film can be wet etched without attacking either the solder or the underlying circuit elements. The thickness of the titanium film is generally between 0.05 and 0.2 micrometers and is readily deposited onto the photoresist protective film. This thickness of titanium is significantly thinner than that of other films used previously as plating membranes. The suitability of a thin titanium film as a membrane for electroplating of solder is

unexpected. The method does not require the use of copper.

III. BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

FIG.1(a) is a schematic diagram showing prior art of fabricating solder bumps by shadow mask evaporation method.

FIG.1(b) is a schematic diagram showing prior art of fabricating solder bumps by electroplating method.

FIG. 2 is a schematic diagram showing a preferred embodiment of the solder bump structure of this invention.

FIG. 2(a) is a plan view of the structure shown on FIG. 2 showing the same structure from above.

FIG. 2(b) is a schematic diagram showing the structure of the preferred embodiment of the underbump metallization layer.

FIG. 3 is a schematic diagram showing a detailed illustration of interface between the solder, the pad, and the solder dam in the solder bump structure of this invention, including the use of a titanium sealant feature.

FIG. 3(a) is a schematic diagram showing a detailed illustration of another variation of interface between the solder, the pad, and the solder dam in the solder bump structure of this invention, including the use of a titanium sealant feature, where the titanium sealant feature occupies the entire interface area between interconnect and the pad.

FIG 3(b) is a schematic diagram showing an illustration of the relative positions of the pad, the titanium sealant feature, and the insulating film, where both the titanium sealant feature and the insulating film are used.

FIG. 4 is a schematic illustration showing an alternative embodiment of the solder bump structure.

FIGs. 4(a) through 4(e) are schematic illustrations each showing alternative embodiments of the plating membrane.

IV. DETAILED DESCRIPTION OF THE INVENTION

1. The Preferred Embodiments.

The preferred solder bump structure of this invention is illustrated in Figures 2, 2(a), and 3. The structure is formed on a substrate 1 that contains either group IV or group III-V semiconductor devices and circuits. The devices and circuits may contain exposed air bridges 2, microelectromechanical elements such as MEMS switches (not shown), and/or optoelectronic devices with exposed optical surfaces and coatings (not shown, either). These devices and circuits typically utilize exposed gold and/or titanium and/or platinum interconnect lines 3. The solder bump defining structure is a multilayer structure. The first layer is preferably an optional patterned insulating film 4 or a sealant feature on top of which the underbump metallization UBM 5 is applied followed by a patterned layer of a photoresist 6 and, finally, by a thin layer 7 of a metal, preferably, titanium.

Preferably the interconnect 3 is at least partially covered by an insulating film 4 in the vicinity of the UBM 5. At least a part of the UBM 5 overlaps the insulating film 4 (FIG. 2). The insulating film 4 is made of an electrically insulating material or dielectric, preferably, silicon nitride or polyimide. The

preferred thickness of the insulating film 4 is within a range of 0.1 to 3.0 micrometers. A via is etched through the insulating film using known photolithographic patterning and etching techniques to allow for an electrical connection between the subsequently deposited UBM 5, which will occupy the via, and the interconnect metal 3.

Alternatively, this alternative being an equally good choice, a patterned sealant feature 7b, made preferably of titanium, occupies the area in the vicinity of the UBM 5, as shown on FIG. 3. This sealant feature 7b preferably extends at least several micrometers beyond the edge or periphery of the UBM 5 and is preferably ring or annular shaped. Alternatively, the titanium sealant 7b can extend entirely or partially underneath the UBM 5 [See FIG. 3(a)]. The preferred thickness of this sealant feature 7b is between about 0.02 and 0.20 micrometers. This sealant feature 7b can be present instead of, or together with, the insulating film 4. If the sealant feature 7b is present together with the insulating film 4, the sealant feature 7b is arranged between the UBM 5 and the insulating film 4, as shown on FIG. 3(b).

The solder bump structure contains a solder pad or UBM 5 that is

formed above or on a portion of the metal interconnect 3. In the preferred embodiment, the UBM 5 is formed over a portion of the insulating film 4. As is described below, with reference to FIG. 2(b) and FIGs. 3, 3(a) and 3(b) the multilayer UBM 5 pad preferably includes an adhesion improvement layer, preferably a layer of titanium 5a; a diffusion barrier layer, preferably a layer of nickel 5b; and a solder-wettable cap layer, preferably a layer of gold 5c. Of course, other metals that serve the same or similar functions, which functions are discussed below in greater detail, could be used instead additionally.

Layer 5a of the UBM 5 is an adhesion improvement layer. It is preferably a layer of titanium that serves to improve adhesion of the pad 5 to the underlying interconnect line 3 of the circuit (See FIGs. 2 and 3). A typical thickness for the adhesion improvement layer 5a is within a preferred range of between 0.02 and 0.05 micrometers. The adhesion improvement layer 5a, in combination with plating membrane 7, also serves to seal gold, often used in interconnect 3, from the solder 9 (See FIG. 2).

Any lead/tin solder that is in contact with gold can rapidly interdiffuse with gold. Such interdiffusion can consume the metal of the interconnect, often gold, and also can degrade the mechanical

and thermal properties of the solder. Therefore, it is desired to isolate the gold in the interconnect 3 from solder 9.

A diffusion barrier layer 5b, preferably a layer of nickel, provides a diffusion barrier that prevents the metal used in interconnect 3 from being attacked by the lead/tin solder 9. A typical thickness for the diffusion barrier layer 5b is preferably within the range of between 0.5 and 1.0 micrometers.

A thin solder-wettable cap layer 5c, preferably a layer of gold, formed above the diffusion barrier layer 5b, serves as a solder-wettable, non-oxidized cap. Cap layer 5c is preferably kept thin so that it can be consumed into the solder when it is subsequently heated without significantly degrading the solder. A typical thickness for the solder-wettable cap layer 5c is preferably within the range of 0.05 and 0.2 micrometers. The UBM pad 5 is formed preferably by evaporation and liftoff. An image-reversal photolithography process is the preferred process to form a UBM pad 5, having a trapezoidal profile, that it is slightly smaller in diameter at the top.

A protective film 6 preferably covers the regions of the circuit that do not contain solder bumps. This protective film 6, which can

be applied either before or after the UBM 5, is present while the remaining parts of the solder bump structure are being formed, and is typically and preferably comprises a layer of a removable photoresist. The protective film 6 should cover all of the elements of the circuit that need to be protected. The thickness of the photoresist is chosen to ensure this coverage and is preferably within the range of between 0.5 and 40 micrometers. The protective layer 6 also serves as a mechanical base for the plating membrane 7. The protective layer 6 is typically contour-baked after it is spun onto the substrate and patterned in order to round any edges in the film which might produce breaks in the plating membrane 7 when that membrane is deposited on it, preferably by evaporation. The protective layer 6 may be formed of other materials, including, as will be seen, a conductive polymer, or a non-conductive material, such as a spin-on glass. The protective layer 6 is patterned in such a way that at least a portion of the UBM 5 is exposed. After a solder bump 8 has been formed by electroplating, the protective film 6 may be removed, preferably by dry etching or with a solvent. The electroplated solder is identified by numeral 8 on FIG. 2.

The film or the plating membrane 7, preferably a titanium film, serves a dual function of being a membrane for electroplating of the solder and of being a non-wettable dam for wetting back of the

electroplated solder 8. The electroplated solder 8 may be disk shaped as shown on Figures 2 and 2(a). The solder 8 is heated to melt it, causing it to wet-back and assume a spherical or dome-like configuration which is identified by a broken line and is marked by numeral 9 on FIG.2, and is identified as a solid line and numeral 9 on FIG. 3. The diameter of such spherical or dome-like structure is usually between 10 and 100 micrometers.

In its role as the plating membrane 7 for electroplating of the solder, the film 7 preferably has a thickness that is sufficient to provide adequate electrical conduction to all of the solder bump sites on a substrate. A thickness of at least several hundred angstroms is often sufficient. Since the film 7 is deposited onto photoresist 6 and should preferably not have unpatterned breaks in it, the thickness of that film should preferably be small enough to avoid producing excessive stress on the film or the photoresist. Thus the thickness should be less than several thousand angstroms. The preferred thickness of the film 7 is, therefore, preferably within a range between 200 and 1,000 Angstroms.

One or more openings or vias 71 are etched in the film 7 to expose a portion of the underlying UBM 5. Preferably, the film 7 initially forms a continuous covering over the entire substrate so that no

solder bump region is located in an isolated island. If a 'spin-on conductive polymer is used as a protective film 6, the thin titanium film need not be used as the conductive plating membrane since the conductive polymer will then provide the electric current conducting path to support the electroplating of solder 8. In this case the titanium film 7 is used as a non-wettable solder dam and only needs to cover a portion of the area around the substrate 1.

After one or more vias 71 have been formed and the solder bump has been electroplated, much of the exposed film 7 is removed, preferably by masking and wet etching or dry etching, preferably leaving only a band of a metal, preferably titanium, 7a that surrounds and partially underlies the disk 8 of solder, as shown by FIGs. 2 and 2(a). This band 7a serves as a non-wettable dam that causes the solder to wet back onto the portion of the UBM 5 that is not covered by the titanium when heated.

The function of the film 7 as a non-wettable dam is illustrated in FIG. 3. The non-wettable dam 7a, in combination with the UBM pad 5 (and the optional sealant feature 7b, if used) completely seals the interconnect metal 3 of the circuit from exposure to the solder 8. The solder, after wet-back, should be in contact only with the thin gold cap 13, which it consumes, the nickel barrier 5b and the dam

7a. Consequently, metal FILM 7 fully covers the sidewalls' of the pad 5 and protects the interconnect 3. A thickness of several hundred angstroms should be sufficient to ensure this coverage if the substrate is held in a rotating planetary fixture as the titanium film is deposited.

As previously indicated, the completed solder bump structure on the circuit substrate is formed by subsequently heating the substrate to melt the solder 8 and wet it back, off the dam 7a and onto the pad 5. Another portion of the solder bump structure is initially formed on a separate substrate 10 that is subsequently bonded to the first substrate by means of the solder, preferably by using heat. This other portion consists of a second UBM pad 11 and a second titanium dam 12.

2. The Alternative Embodiments.

Several other embodiments of the solder bump structure are described below. These embodiments either are simplified versions of the preferred structure or they are variations in which some element of the structure is modified. In one embodiment, the circuit does not have any elements that need to be protected by a removable protective film 6. Consequently, that film is not present and the plating

membrane 7 is deposited directly onto the circuit substrate.

Another embodiment is illustrated in FIG. 4. In this embodiment, the film 7 instead of fully covering the sidewalls of the UBM pad 5 covers only the bottom portion of that pad. The solder 8 then covers the sidewalls as well as the top of the UBM pad. The solder, however, would still be sealed from the interconnect metal 3.

This embodiment is especially useful in, but not restricted to, those cases for which the protective film 6 is unnecessary or undesirable. The film 7 can be deposited underneath the UBM 5, in which case the film 7 could be integral with the titanium lower layer 5a of the UBM 5 and the optional sealant feature 7b.

Both the film 7 and the UBM 5 can be patterned by liftoff. In a variation of the solder bump structure, chrome is used instead of titanium as the material for the membrane 7, as shown on FIG. 4(a). In another variation, a multilayer film for the membrane 7 is used. The examples of materials used to make such multilayer film comprise, but are not limited to, titanium-nickel-titanium, as shown on FIG. 4(b); titanium-nickel-chrome, as shown on FIG. 4(c); titanium-platinum-titanium, as shown on FIG. 4(d); or titanium-nickel-oxidized silicon, as shown on FIG. 4(e).

Having described the invention in connection with several embodiments thereof, modification will now suggest itself to those skilled in the art. As such, the invention is not to be limited to the described embodiments except as required by the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237